



# Zenith Narrowline Sliding Glass Door

Natural Light with Unobstructed Views, for Every Space

With its sleek frame and sightlines, the Narrowline allows for expansive, uninterrupted views - even in smaller openings. The Narrowline provides outstanding energy efficiency with some of the lowest U-Factors in the industry, making it a top choice for those seeking optimal performance in their building designs.



- **Superior Energy Efficiency:** U-Factors that outperform competing doors.
- **Modern Aesthetic:** Slim sash profile offers maximum daylight and views in smaller openings.
- **Sleek Look:** Clean sightlines offer a modern, but timeless appeal.
- **Heavy Duty Performance:** Robust rollers for smooth, effortless sliding.
- **Extra Durable:** Fiberglass frame, sash, and interlock offer increased resistance to the elements
- **Abundant Fresh Air:** Enjoy a sliding screen and a wide, unobstructed opening.

## Frame Colors



## Handle Options



Optional auxiliary foot lock comes in black and white.

## Narrowline Full Frame Thermal Performance Data *ThinGlass Triple (TGT) / ThinGlass Quad (TQ)*

ZR-6 Glass				ZR-9 Glass			
Glass Type	U-Factor	SHGC	VT	Glass Type	U-Factor	SHGC	VT
Balanced-6 TGT	0.18	0.27	0.43	Balanced-9 TQ	0.15	0.25	0.40
SolarControl-6 TGT	0.18	0.19	0.43	SolarControl-9 TQ	0.15	0.17	0.40
HighGain-6 TGT	0.18	0.43	0.52	HighGain-9 TQ	0.16	0.40	0.49

\*Thermal performance results calculated according to NFRC. NFRC and Energy Star Certification is underway.

## Narrowline Size Options

Configuration	Standard Sizes	Min. Width	Min. Height	Max. Width	Max. Height	Max. Opening (ft <sup>2</sup> )	Max. Panel Size (ft <sup>2</sup> )
OX/XO	6068 6080 8068 8080	48"	48"	96"	96"	56	30
OOX/XOO	9068 12080	74"	48"	120"	96"	70	30
OXO	12068 12070	74"	48"	144"	96"	84	30
OXXO	12068 12080	96"	48"	144"	96"	84	30

OX/XO Maximum



OXXO Maximum

